



OILS FOR ROTTNE MACHINES 2008-04-21

Oils according to list Q8 2008 can be used on Rottne machines.

The engine is at the delivery filled with a special breaking-in oil, which shall be changed after 100 hours. It is not permitted to run the engine with another type of oil during the first 100 hours.

Mixing with different types of oils is forbidden - both in the system and the components. If the machine is delivered with BP, it is necessary to use BP until a complete change could be done.

Only John Deere Cool Gard or Glysantin G 05 is permitted for the cooling system as long as the engine guarantee is valid.

Best regards
ROTTNE INDUSTRI AB

Mikael Edh
Service Manager

Rottne Industri AB

2008

Smörjställe/ Application	Rottne Specifikation/ Rottne Requirement	Produkt/ Product	Viskositet/ Viscosity
Standard: (-25°C)			
Motor / Engine Ford och Iveco John Deere	API CD/CE/CF-4 API CF-4/CG-4, ACEA E2/E3 API CH-4/CI-4	Q8 T 1000 / T 1000 (D) Q8 T 800	10W-30 10W-40
John Deere Genset euro II	ACEA: E4/E5 500 t bytesintervall med longlife filter 500 h oil drain interval with longlife filter	Q8 T 800	10W-40
John Deere Genset euro III	ACEA: E6/E7 500 t bytesintervall med longlife filter 500 h oil drain interval with longlife filter	Q8 T 905	10W-40
Arctic: (-35°C)			
John Deere Tier III	ACEA E6/E7 500 t oil drain interval with longlife filter 500 h oil drain interval with longlife filter	xxxxxxx	5W-30 / 5W-40
Standard: (-25°C)			
Axlar / Axles Fördelningsväxellåda (ej F9/F12) fram- och bakaxlar, boggieaxlar, vridhus	API GL-5	Q8 T 55 Q8 Trans XGS / Q8 T 65	80W-90 75W-90
Transfer case (not F9/ F12) front- and rearaxel, boggieaxel crane swingbase	API GL-5	Q8 T 55 Q8 Trans XGS / Q8 T 65	80W-90 75W-90
Axelhus boggi F12-S och SMV Rapid	API GL-5	Q8 Trans XGS / Q8 T 65	75W-140
Axelhouse bogie F12-S and SMV Rapid	API GL-5	Q8 Trans XGS / Q8 T 65	75W-140
Fördelningsväxellåda F9/F12 -PowerShift- och drevhus	GM Dexron II	Q8 Auto 14 Q8 Auto 15 Q8 Auto 15 ED	
Transfer gearcase F9/ F12 -PowerShift- and coghouse			
Arctic: (-35°C)			
Fördelningsväxellåda, boggie, differential, Vridhus	API GL-5	Q8 Trans XGS / Q8 T 65	75W-90
Transfer case, bogie, differential, Crane swing base			
Standard: (-20°C)			
Hydrostat / Hydrostatic transmission	API CD/CE	Q8 T 1000 / T 1000 (D)	10W-30
Arctic: (-35°C)			
		Q8 Auto 15/ Q8 Auto 15 ED	
Standard: (-25°C)			
Hydraulsystem / Hydraulic system	SS 155434 AV46 SS 155434 BV46 Miljöanpassad	Q8 Hindemith 32-68 Q8 Holbein Bio Plus / Holbein NWG Q8 Handel Q8 Heller	ISO VG 46 ISO VG 46 ISO VG 46 ISO VG 46
Arctic: (-35°C)			
		Q8 Hindemith LT Q8 Handel Q8 Heller	ISO VG 32 ISO VG 32 ISO VG 32
Momentförstärkare Clark Converter			
	GM Dexron II	Q8 Auto 14 Q8 Auto 15 Q8 Auto 15 ED	
Sågkedja/ Chainsaw			
		Q8 Bizet AW 68 Q8 Bizet Bio Q8 Chain Oil Bio	ISO VG 68 ISO VG 68 ISO VG 68
Standard: (-25°C)			
Fett / Grease points	Litium NLGI 2	Q8 Rembrandt EP2 Q8 Rubens WB Q8 Rubens LT Q8 Renoir	
Arctic: (-35°C)			
	Litium NLGI 2	Q8 Rubens LT	NLGI 2
Standard: (-25°C)			
Kylarvätska / Cooling John Deere Ford, Iveco	JD Approved BS 6580 , SAE J-1034	xxxxxxx OKQ8 Glykol/ Q8 Antifreeze	
Arctic: (-35°C)			
	JD approved	John Deere Cool Gard	