

Q8 SuperGear V 75W-80

Description

Synthetic high performance transmission fluid.

Application

- Manual transmissions in heavy duty vehicles

Recommendations

- Q8 SuperGear V can be used in transmissions when one or more of the following specifications are used to describe the required lubricant quality:

Specifications

- API GL-4
- Volvo 97307
- MAN 341 ZE_VR (former MAN 341 SL)
- Voith Retarder Oil Class C
- Eaton S Series transmissions
- ZF TE-ML-02B (ZF Ecomid and Ecosplit, but only after 7500 km)
- DAF

Benefits

- Limits synchromesh wear
- Provides smooth synchromesh gear shifting
- Facilitates equipment cold starting
- Protects against wear
- Keeps transmission clean
- Prevents corrosion
- Protects against rust
- Extends equipment life
- Offers fuel economy

Properties	Method	Unit	Typical
Viscosity Grade			SAE 75W-80
Absolute Density, 15 °C	D 4052	kg/m ³	860
Kinematic Viscosity, 40 °C	D 445	mm ² /s	66.2
Kinematic Viscosity, 100 °C	D 445	mm ² /s	10.5
Viscosity Index	D 2270	-	148
Brookfield Viscosity, -40 °C	D 2938	Pa.s	32.2
Flash Point, P-M	D 93	°C	188
Pour Point	D 97	°C	-55

The figures above are not a specification. They are typical figures obtained within production tolerances.

