

# Q8 Antifreeze Long Life Premixed

## Description

Q8 Antifreeze Long Life Premixed forms a cooling liquid based on mono ethylene glycol that transfers the heat of the combustion engine to the radiator and which protects the engine against corrosion, freezing and boiling.

The Long Life of the coolant is obtained by non-depleting corrosion inhibitors.

Q8 Antifreeze Long Life Premixed is amine-, nitrite-, phosphate-, borate- and silicate free.

Q8 Antifreeze Long-Life Premixed is a ready to use engine coolant formulated with the same corrosion inhibitor technology.

## Application

- Q8 Antifreeze Long Life Premixed can be used in cooling systems of all automotive passenger cars, commercial vehicles, buses and stationary internal combustion engines.
- It can also be used in most types industrial heat transfer and cooling systems.

## Recommendations

- Replacement of the antifreeze is recommended after 4 years.
- Mixing with non-long life engine coolants will spoil the long life feature although Q8 Antifreeze Long Life Premixed is compatible with most other ethylene glycol based engine coolants.

## Specifications

• Q8 Antifreeze Long Life Premixed is an OAT (Organic Acid Technology) based engine coolant fluid and has been accepted by most institutions and engine and vehicle manufacturers. The important ones are:

- ASTM D3306
- ASTM D4985/D6210
- NATO S-759
- MAN 324 SNF(Appr.)
- VW/Audi/Seat TL774D(G12) & TL774F(G12+)
- VW TL774G (G12++)
- SAE J1034
- JASO M325
- Opel QL130100
- John Deere H24B1/C1
- BS 6580
- Önorm V5123
- GM6277M
- Afnor R15-601
- Cummins 90T8-4
- Renault 41-01-001/- -S Type D
- Mercedes 325.3
- FVV Heft R443
- Ford WSS-M97B44-B/D
- Ford CRM 8229
- Volvo 128 6083 / 002
- DAF 74002
- PSA B715110
- Scania TB 1451
- Mitsubishi MHI (Volvo engines)
- MTU MTL 5048

## Benefits

- Provides long life protection against all forms of corrosion
- Reduces repairs of thermostat, radiator and water pump thus cost and downtime

- Improved hard water stability due to the absence of silicates and phosphates
- One product for passenger cars, commercial vehicles, buses and stationary engines
- Effectively protects aluminium against high temperature corrosion
- Synergistic effects provides superior and extended corrosion protection
- Prevents cavitation corrosion even without coolant supplements
- The corrosion inhibitor package is environmentally friendly

| Properties                 | Method | Unit              | Typical    |
|----------------------------|--------|-------------------|------------|
| Density, 15 °C             | D 1122 | kg/m <sup>3</sup> | 1.057      |
| Freezing Protection 50/50% | D 1177 | °C                | -38        |
| Colour                     | Visual |                   | Orange-red |

*The figures above are not a specification. They are typical figures obtained within production tolerances.*