

# Q8 T 3500

## Description

Wet brake oil for lubrication of Kessler wet brake systems.

### **Application**

• For equipment such as Straddle-Carriers and Heavy-Duty Fork Lift Trucks equipped with wet brake systems from Kessler.

#### **Specifications**

Kessler & Co GmbH Approval

#### **Benefits**

- Optimal frictional characteristics
- · Reduces wet brake noise, thus maintains brake capacity while limiting friction plate wear
- Provides good transmission lubrication
- Protects equipment against rust
- Prevents equipment component corrosion
- Suitable for use as hydraulic fluid
- · Contains effective anti-foam agent
- Compatible with conventional elastomers, thus avoiding leakage

| Properties                  | Method | Unit  | Typical |
|-----------------------------|--------|-------|---------|
| Absolute Density, 15 °C     | D 1298 | kg/m³ | 863     |
| Kinematic Viscosity, 40 °C  | D 445  | mm²/s | 28.3    |
| Kinematic Viscosity, 100 °C | D 445  | mm²/s | 6.0     |
| Viscosity Index             | D 2270 | -     | 168     |
| Flash Point, P-M            | D 93   | °C    | 199     |
| Pour Point                  | D 97   | °C    | -36     |

The figures above are not a specification. They are typical figures obtained within production tolerances.