

# Q8 Rossini G 150

### Description

Food grade gear lubricant

### Application

- The main application is the lubrication of gear drives and bearings in general and in particular in food and pharmaceutical Industry. They are used where anti-wear and EP properties are needed because of the load carrying power as in meat and poultry plants.
- Q8 Rossini G are long-life fluids formulated by adding to synthetic hydrocarbon base fluids specially selected components for giving improved lubrication at high and low temperatures, minimum volatility and excellent protection against corrosion and oxidation.
- Q8 Rossini G are formulated using substances permitted by FDA CFR 21 and are approved by NSF as category H1 food grade lubricants for having incidental contact with food.

### Specifications

- DIN 51517 Part 3, category CLP

### Benefits

- Long-life gear lubricants
- Strong protection towards high loads
- Less maintenance / costs
- Compatible with mineral oils
- Compatible with normally used elastomers
- Excellent thermal and chemical stability
- Energy saving and friction reduction
- Outstanding low temperature start ability
- Reduced oil consumption

### References

- NSF registration number for Q8 Rossini G 150 is 136414

Properties	Method	Unit	Typical
ISO Viscosity Grade	-	-	150
Absolute Density, 15 °C	D 4052	kg/m <sup>3</sup>	845
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	151
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	18.9
Viscosity Index	D 2270	-	142
Flash Point	D 92	°C	275
Pour Point	D 97	°C	-39
FZG Test, A/8.3/90	DIN 51354	load stage	> 12

*The figures above are not a specification. They are typical figures obtained within production tolerances.*



