

# Q8 Rembrandt EP 00 WV

### Description

Q8 Rembrandt EP 00 WV is a multi-purpose grease with EP properties. High quality lithium thickened lubricating grease based on mineral oil.

### Application

- Q8 Rembrandt EP 00 WV is recommended for:
- Willy Vogel centralised lubrication systems,
- Tecalomit,
- Mercedes Benz MB 264,
- MAN 283,
- Lincoln,
- But also lightly loaded closed gears.

### Specifications

- Q8 Rembrandt EP 00 WV classifications:
- DIN 51825 KP00 G-30
- ISO 6743-9 ISO-L-XCBE00

### Benefits

- Easy pumpability at low temperatures due to its smooth structure
- Excellent load carrying capacity
- Outstanding stability and long service life
- Suitable over a wide temperature range (from -40°C up to 110 °C)

Properties	Method	Unit	Typical
Soap type	-	-	Lithium
Consistency, NLGI No.			NLGI 00
Penetration, Worked, 25 °C, 150 g, 5 s	D 217	-	
60 strokes		0.1 mm	415
Colour	Visual	-	Light brown
Dropping Point	D 566	°C	>160°C
Copper Corrosion, 100 °C, 24 h	D 4048	-	pass
Water Resistance, 90 °C, 3 h	DIN 51807	-	pass
SKF Emcor Test, Distilled Water	ISO 11007	-	0-0
Four Ball, Weld Load	IP 239	N	2400
Kin. Viscosity Base Oil at 40 °C	D 445	mm <sup>2</sup> /s	40
Kin. Viscosity Base Oil at 100 °C	D 445	mm <sup>2</sup> /s	5

The figures above are not a specification. They are typical figures obtained within production tolerances.

