

Q8 Gear Oil XG 80W-90

Description

Automotive universal transmission lubricant

Application

- In synchronised and non-synchronised manual transmissions, axles and drive line components requiring API GL-4/GL-5 performance level.
- Approved by Scania in certain categories for use in extended drain application (180000 km).

Specifications

- API GL-4, API GL-5
- Scania STO 1:0
- SAE J 2360 (PRI GL 0208)
- MAN 341 Typ E2/Z2
- MAN 342 Typ M2
- ZF TE-ML 02B
- ZF TE-ML 05A
- ZF TE-ML 12L
- ZF TE-ML 12M
- ZF TE ML 16B
- ZF TE-ML 17B
- ZF TE-ML 19B
- ZF TE-ML 21A

Benefits

- Universal transmission oil
- Extended drain capability
- Excellent gear shifting
- Prevents against synchromesh wear
- Extends equipment life
- Protects against gear wear
- Stay-in grade shear stability
- Prohibits corrosion
- Protects against rust

Properties	Method	Unit	Typical
Viscosity Grade			SAE 80W-90
Absolute Density, 15 °C	D 1298	kg/m ³	896
Kinematic Viscosity, 40 °C	D 445	mm ² /s	155.5
Kinematic Viscosity, 100 °C	D 445	mm ² /s	15.5
Viscosity Index	D 2270	-	101
Brookfield Viscosity, -26 °C	D 2938	Pa.s	129000
Flash Point, P-M	D 93	°C	173
Pour Point	D 97	°C	-24

The figures above are not a specification. They are typical figures obtained within production tolerances.

