

# Q8 Unishift PC 75W

### Description

Universal automotive passenger car and light duty transmission lubricant

### Application

- Q8 Unishift PC SAE 75W was developed as a multi-vehicle manual transmission oil for passenger car and light duty transmissions covering a wide range of vehicle brands.
- Q8 Unishift PC SAE 75W is recommended for most vehicles in use that are out of warranty and no longer require the OEM genuine oil.
- Q8 Unishift PC SAE 75W may be used as gear lubricant in manual transmissions for the following specifications and vehicle brands:

API GL-4

Ford WSD-M2C200-D2

Nissan API GL-4

Toyota API GL-4/GL-5

Seat API GL-4

Volkswagen API GL-4

### Benefits

- Specifically developed for passenger car and light duty automotive transmissions
- Recommended for most passenger car manual transmissions
- Provides excellent low temperature fluidity
- Facilitates gear shifting at low temperatures
- Suitable for extended application periods
- Reduces drive-line operating temperatures
- Reduces internal friction
- Protects against gear wear
- Extends equipment life
- Prohibits corrosion
- Protects against rust

Properties	Method	Unit	Typical
Viscosity Grade			SAE 75W
Absolute Density, 15 °C	D 1298	kg/m <sup>3</sup>	847
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	27
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	5.7
Viscosity Index	D 2270	-	158
Brookfield Viscosity, -40 °C	D 2938	Pa.s	45
Flash Point	D 93	°C	195
Pour Point	D 97	°C	-39

The figures above are not a specification. They are typical figures obtained within production tolerances.

