

## Q8 Copper Thread

### Description

Multi purpose anti-seize grease

### Application

- Anti-seize grease for all types of threaded connections. It is suitable for use, as an anti-seize up to 1100°C, and will protect against seizure due to corrosion and chemical attack. Typical applications include pipe fittings and valves in the petrochemical industries and on drilling equipment.

### Benefits

- Prevents seizure during assembly and reduces therefore assembly time
- Enables easy dismantling of components subjected to high temperatures
- Provides an effective anti-seize in saturated conditions, including chemical environments and salt water
- Enables fast and easy dismantling of parts, allowing them to be reused after dismantling

### User Instructions

- Apply by brush to the threaded components prior to assembly. Ensure that both threaded surfaces are completely coated with grease.

| Properties                             | Method | Unit   | Typical         |
|--|--------|--------|-----------------|
| Soap type                              | -      | -      | Bentonite       |
| Consistency, NLGI No.                  | -      | -      | 1 / 2           |
| Colour                                 | Visual | -      | Copper coloured |
| Four Ball, Weld Load                   | IP 239 | kg     | 350             |
| Penetration, Worked, 25 °C, 150 g, 5 s | D 217  | 0.1 mm | 300             |
| Dropping Point                         | D 2265 | °C     | >300            |

*The figures above are not a specification. They are typical figures obtained within production tolerances.*

