

# Q8 Mozart HPX 40

## Description

Diesel engine lubricant

## Application

- In all turbo-charged high performance four stroke diesel engines in use as propulsion engines for barges, fishing vessels, off-shore vessels, as auxiliary engines on deep-sea going vessels or as prime movers in power stations

## Recommendations

- Q8 Mozart HPX is developed for direct injected turbo-charged diesel engines operating on low sulphur fuels under severe operating conditions
- Q8 Mozart HPX may be used as engine or transmission lubricant, when one or more of the following specifications are used to describe the required lubricant quality:

## Specifications

- API CD
- MIL-L-2104C
- MWM-B cleanliness min. 70

## Benefits

- Good bore-polishing protection
- Protects against wear, corrosion and rust
- Provides good engine cleanliness
- Protects against liner lacquering
- Good water separation and alkalinity retention
- Readily cleaned by centrifuge
- Excellent oxidation and thermal stability
- Extending oil drain periods
- Also suitable as a transmission lubricant

Properties	Method	Unit	Typical
Viscosity Grade			SAE 40
Absolute Density, 15 °C	D 4052	g/ml	0.898
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	14.6
Flash Point, P-M	D 93	°C	202
Pour Point	D 97	°C	-12
Total Base Number	D 2896	mg KOH/g	10.0
Sulfated Ash	D 874	% mass	1.1

*The figures above are not a specification. They are typical figures obtained within production tolerances.*

