

Q8 T 100 SAE 40

Description

Engine lubricant

Application

- In four stroke gasoline and normally aspirated diesel engines operating under mild to moderate conditions

Recommendations

- Q8 T 100 may be used as lubricant in gasoline and normally aspirated diesel engines, when one or more of the following specifications are used to describe the required lubricant quality:

Specifications

- API CC/SE
- MIL-L-2104B

Benefits

- Economy grade for mild to moderate operating conditions
- Especially suitable for older (pre 1976) engines
- Provides satisfactory lubrication
- Keeps engines clean
- Limits engine wear
- Prohibits corrosion
- Protects against rust

Properties	Method	Unit	Typical
Viscosity Grade			SAE 40
Absolute Density, 15 °C	D 1298	kg/m ³	889
Kinematic Viscosity, 40 °C	D 445	mm ² /s	147.7
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.67
Viscosity Index	D 2270	-	98
Borderline Pumping Temperature	D 4684	°C	-
Flash Point, P-M	D 93	°C	218
Pour Point	D 97	°C	-12
Total Base Number	D 2896	mg KOH/g	5.0
Sulfated Ash Content	D 874	% mass	1.0

The figures above are not a specification. They are typical figures obtained within production tolerances.

