

# Q8 Chopin 150

## Application

- Pneumatic tools and rock drill equipment
- Specification: ISO 6743-11, category PAC-PBC

## Benefits

- No harmful or unpleasant odours due to careful component selection
- Outstanding protection against wear, rust and corrosion even in the presence of condensed water
- Excellent icing prevention through emulsification of water droplets
- High resistance against washing effect of water through strong oil film

## References

- Q8 Chopin meets the specifications for pneumatic tool lubricants of leading manufacturers among which are Atlas Copco and Gardner Denver

Properties	Method	Unit	Typical
ISO Viscosity Grade	-	-	150
Absolute Density, 15 °C	D 4052	kg/m <sup>3</sup>	888
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	150
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	14.5
Flash Point	D 93	°C	251
Flash Point	D 92	°C	282
Pour Point	D 97	°C	-15
Appearance, 48 h, 4 °C	Visual	-	bright
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Saponification Number	D 94	-	3.0
Phosphorus	XRF	% mass	0.04
Four Ball, Weld Load	D 2783	N	1700

*The figures above are not a specification. They are typical figures obtained within production tolerances.*