

# Q8 T 65 LS 75W-90

### Description

Synthetic automotive gear lubricant for Limited Slip differentials.

### Application

- For transmissions where an oil with "Limited Slip" is required.
- Q8 T 65 LS is recommended for transmissions where one of the following specifications is required:

API GL-5

MIL-L-2105B

Ford ESW-M2C119-A

Ford ESP-M2C154-A

General Motors Pt. no. 19 42 382 (90 006 326)

Hanomag Specification 511

Volvo 97311

ZF TE-ML 05D

ZF TE-ML 12D

ZF TE-ML 16F

### Benefits

- Full synthetic formulation to provide an extreme thermal stability.
- Superior lubrication in heavy duty conditions due to the synthetic formulation.
- Proven in Rallye Racing.
- Contains a special friction modifier additive to assure an optimal "Limited Slip".
- Reduction of noise in the transmission.
- Extends driveline component life
- Prohibits corrosion.

Properties	Method	Unit	Typical
Viscosity Grade			SAE 75W-90
Absolute Density, 15 °C	D 1298	kg/m <sup>3</sup>	860
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	102
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	15.0
Viscosity Index	D 2270	-	153
Brookfield Viscosity, -40 °C	D 2983	Pa.s	135
Pour Point	D 97	°C	-42
Flash Point, COC	D 92	°C	196

The figures above are not a specification. They are typical figures obtained within production tolerances.

