

Q8 Trans XGS 75W-90

Description

Synthetic automotive gear lubricant

Application

- In heavy duty drive-line components such as rear-axes, final drives and selected manual transmissions, requiring special low temperature fluidity to reduce fuel consumption or facilitate gear shifting

Specifications

- API GL-4, API GL-5
- SAE J 2360
- MB-Approval 235.8
- Scania STO 1:0
- Volvo Transmission Oil 97312
- ZF TE-ML 02B
- ZF TE-ML 05B
- ZF TE-ML 12B
- ZF TE-ML 16F
- ZF TE-ML 17B
- ZF TE-ML 19C
- ZF TE-ML 21B
- MAN 3343 Typ S
- MAN 341 Typ E3
- MAN 342 Typ M3

Benefits

- Provides excellent low temperature fluidity
- Facilitates gear shifting at low temperatures
- Reduces drive-line operating temperatures
- Reduces internal friction
- Provides good wear protection under heavy duty condition
- Extends drive-line component life
- Prohibits corrosion
- Protects against rust

Properties	Method	Unit	Typical
Viscosity Grade			SAE 75W-90
Absolute Density, 15 °C	D 1298	kg/m ³	869
Kinematic Viscosity, 40 °C	D 445	mm ² /s	108
Kinematic Viscosity, 100 °C	D 445	mm ² /s	15.6
Viscosity Index	D 2270	-	153
Brookfield Viscosity, -40 °C	D 2938	Pa.s	70
Flash Point	D 92	°C	175
Pour Point	D 97	°C	<-51

The figures above are not a specification. They are typical figures obtained within production tolerances.

