

Q8 Auto 25

Description

Fuel economy improving synthetic automatic transmission fluid for Mercedes-Benz using factory fill technology

Application

- MB Approval 236.14 for 7-speed Mercedes-Benz automatic transmissions
- MB 236.12
- For 5-speed Mercedes Benz automatic transmissions type 722.6 with rear wheel drive

Benefits

- Fuel economy improving technology
- Extended drain intervals
- Outstanding resistance against wear and extends transmission life
- Reduces sludge and varnish build-up
- Excellent oxidation and thermal stability
- Outstanding frictional performance
- Improved shear stability for a stable viscosity during use
- Provides immediate lubrication after cold start
- Excellent protection against rust and corrosion
- Outstanding elastomer compatibility

Properties	Method	Unit	Typical
Absolute Density, 15 °C	D 4052	kg/m ³	847
Kinematic Viscosity, 40 °C	D 445	mm ² /s	29.5
Kinematic Viscosity, 100 °C	D 445	mm ² /s	6.4
Viscosity Index	D 2270	-	185
Brookfield Viscosity, -40 °C	D 2893	Pa.s	8.5
Pour Point	D 97	°C	-51
Flash Point	D 92	°C	>200

The figures above are not a specification. They are typical figures obtained within production tolerances.

