

Q8 Auto 15 S

Description

Full-synthetic automatic transmission fluid with extended drain capability

Application

- In ZF automatic transmissions of buses, commercial vehicles, off-highway/construction and military equipment where severe operating conditions prevail or extended drain intervals are applied
- Q8 Auto 15 S is specifically designed for ZF Ecomat Transmissions requiring ZF TE-ML 14 ATF specification offering a drain interval of 120.000km.

ZF TE-ML 14C, 120.000km drain interval for ZF Ecomat Transmissions

ZF TE-ML 20C, 120.000km drain interval for ZF Ecolife Transmissions

Voith 55.6336

MAN 339 V-2/Z-3

Allison TES-295

Allison TES-389

Dexron IIIIG suitable for use

Benefits

- Full synthetic formulation for superior stability
- Extended drain intervals
- Outstanding resistance against wear and extends transmission life
- Reduces sludge and varnish build-up
- Excellent oxidation and thermal stability
- Outstanding frictional performance
- Improved shear stability for a stable viscosity during use
- Provides immediate lubrication after cold start
- Excellent protection against rust and corrosion
- Outstanding elastomer compatibility

Properties	Method	Unit	Typical
Density, 15 °C	D 4052	kg/m ³	850
Kinematic Viscosity, 40 °C	D 445	mm ² /s	37.4
Kinematic Viscosity, 100 °C	D 445	mm ² /s	7.4
Viscosity Index	D 2270	-	171
Brookfield Viscosity, -40 °C	D 2893	Pa.s	8.5
Pour Point	D 97	°C	-48
Flash Point	D 92	°C	>200

The figures above are not a specification. They are typical figures obtained within production tolerances.

