

# Q8 Outboard 4T 10W-40

## Description

Four-stroke SAE 10W-40 High Performance Outboard Engine Oil

## Application

- High-Performance Four-stroke outboard engines requiring NMMA latest FC-W lubricant specifications operating in fresh and salt water conditions
- For all other High-Performance Four-stroke outboard engines requiring optimal engine lubrication protection and engine cleanliness operating in fresh and salt water conditions

## Specifications

- Meets and exceeds latest NMMA specifications for modern four stroke cycle water cooled gasoline engines.
- API SL.

## Benefits

- Excellent rust protection in salt water environments
- Highly stable stay-in-grade viscosity offering extended engine lubrication protection
- Effective cylinder protection against scuffing wear
- Advanced additive technology providing excellent detergency
- Prevents piston ring-sticking and deposit build-up for excellent engine cleanliness

Properties	Method	Unit	Typical
Viscosity Grade			SAE 10W-40
Density, 15 °C	D 1298	kg/m <sup>3</sup>	875
Viscosity, Kinematic, 40 °C	D 445	mm <sup>2</sup> /s	87.7
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	13.3
Viscosity Index	D 445	-	152
Apparent Viscosity, -25 °C	D 5293	mPa.s	6800
Flash Point, COC	D 92	°C	210
Pour Point	D 97	°C	-21
Total Base Number	D 2896	mg KOH/g	7.1

*The figures above are not a specification. They are typical figures obtained within production tolerances.*