

Q8 Ruysdael WR 2

Application

- Universal grease for lubrication of heavily loaded plain- and roller bearings at normal temperatures and limited speeds as well as for the lubrication of water pumps, chassis etc.

Specifications

- Q8 Ruysdael WR 2 classifications:
DIN 51502 KP2K-20
ISO 6743 ISO-L-XBCIB2

Benefits

- Excellent adhesion properties
- Extremely good water resistance
- Long service life
- Rust protection under dynamic and static conditions
- Suitable for heavily loaded plain- and roller bearings at normal temperatures (to +90 °C for WR 0, to +100 °C for WR 1, and to +120 °C for WR 2) and limited speeds

Properties	Method	Unit	Typical
Soap type	-	-	
Consistency, NLGI No.			NLGI 2
Penetration, Worked, 25 °C, 150 g, 5 s	D 217		
60 strokes	-	0.1 mm	286
10000 strokes	-	0.1 mm	281
Copper Corrosion, 100 °C, 24 h	D 4048	-	pass
Dropping Point	D 566	°C	150
SKF Emcor Test, Distilled Water	ISO 11007	-	pass
SKF Emcor Test, WWO, dist. water	-	-	pass
SKF Emcor Test, WWO, synth. salt water	-	-	-
SKF R2F Conditions A	-	-	pass
SKF R2F Test, conditions B, 120 °C	-	-	pass
SKF WBG test, vibrated	-	-	pass
Water Washout Resistance,	D 1264	%	< 5
Kin. Viscosity Base Oil at 40 °C	D 445	mm ² /s	790

The figures above are not a specification. They are typical figures obtained within production tolerances.

